

Forged Pear Shape Link (TH-34)

锻造梨形环

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.

表面喷塑，颜色可选。
体上显示工作载荷。
最大保证载荷为工作载荷的2.5倍。

Size 规格	W.L.L (lbs) Alloy (5:1) 合金钢工作载荷(磅)	W.L.L (lbs) Alloy (5:1) 碳钢工作载荷(磅)	Dimension (mm) 主要尺寸				N.W. (kg/pc) 净重(千克/件)
			A	B	C	D	
3/8"	3600	1800	10	28.5	19	10	0.1
1/2"	7000	2900	12.5	38	25.5	12.5	0.25
5/8"	9000	4200	16	47.5	32	16	0.5
3/4"	12300	6000	19	57	38	19	0.8
7/8"	14000	8300	22	67	44.5	22.2	1.4
1"	24360	10800	25	76	51	25.4	1.9
1-1/8"	30600	12000	28	86	57	28.5	2.92
1-1/4"	36000	16750	32	95	63.5	31.75	3.75
1-3/8"	43000	20500	35	105	70	35	5.12
1-1/2"	54300	25000	38	114	76	38	6.5

G80 Welded D Ring (TH-35)

G80焊接D形环

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.

表面喷塑，颜色可选。
体上显示工作载荷。
最大保证载荷为工作载荷的2.5倍。
最小破断强度为工作载荷的4倍。

Size 规格	W.L.L (t) 工作载荷(吨)	B.L (t) 破断载荷(吨)	Dimension (mm) 主要尺寸			N.W. (kg/pc) 净重(千克/件)
			A	B	D	
14-8	2.5	10	65	55	14	0.3
17-8	4.0	16	62	64	17	0.5
19-8	6.5	26	80	72	19	0.7
22-8	8.0	32	90	76	22	1.0

G80 Forged D Ring (TH-36)

G80锻造D形环

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.

表面喷塑，颜色可选。
体上显示工作载荷。
最大保证载荷为工作载荷的2.5倍。
最小破断强度为工作载荷的4倍。

Size 规格	W.L.L (t) 工作载荷(吨)	B.L (t) 破断载荷(吨)	Dimension (mm) 主要尺寸			N.W. (kg/pc) 净重(千克/件)
			A	B	D	
2.5T	2.5	10	65	55	14	0.3
4.0T	4	16	62	64	17	0.48
6.5T	6.5	26	80	72	19	0.71
8.0T	8.0	32	90	76	22	1.0



Forged Delta Ring (TH-37)

锻造三角环

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.

表面喷塑，颜色可选。
体上显示工作载荷。
最大保证载荷为工作载荷的2.5倍。
最小破断强度为工作载荷的4倍。

Size 规格	W.L.L (lbs) 工作载荷(磅)	B.L (lbs) 破断载荷(磅)	Dimension (mm) 主要尺寸			N.W. (kg/pc) 净重(千克/件)
			D	Φ	L	
3"	4500	18000	79	14	96	0.66
4"	5000	20000	110	16	118.5	0.38



Forged Round Ring (TH-38)

锻造圆环

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 6 times of the W.L.L.

表面喷塑，颜色可选。
体上显示工作载荷。
最大保证载荷为工作载荷的2.5倍。
最小破断强度为工作载荷的6倍。

Size 规格	W.L.L (t) 工作载荷(吨)	B.L (t) 破断载荷(吨)	Dimension (mm) 主要尺寸		N.W. (kg/pc) 净重(千克/件)
			A	B	
3/8*2	0.5	3	10	50	0.11
1/2*2	1	6	13	50	0.21
5/8*3	1.5	9	16	76	0.46
5/8*3-5/16	1.5	9	16	84	0.5
3/4*3	2.3	13.8	19	76	0.67
3/4*4	2.5	15	19	102	0.84
7/8*4	3.3	19.8	22	102	1.2
7/8*5-1/2	2.5	15	22	140	1.55
1*4	4.9	29.4	25	102	1.59
1*5-1/2	4.9	29.4	25	140	2.1
1-1/8*6	4.7	28.2	28	152	2.87
1-1/4*5	7.7	46.2	32	127	3.1
1-1/4*6	7.7	46.2	32	152	3.6
1-1/4*10	7.7	46.2	32	254	5.6
1-3/8*6	8.6	51.6	35	152	4.5
1-1/2*8	11.3	67.8	38	203	6.8
1-1/2*8-3/4	11.3	67.8	38	222	7.32
1-1/2*10	11.3	67.8	38	254	8.22
2*12	15.9	95.4	50	305	17.8

G80 Eye Hook with Latch (TH-39)

G80眼型吊钩

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.

表面喷塑，颜色可选。
体上显示工作载荷。
最大保证载荷为工作载荷的2.5倍。
最小破断强度为工作载荷的4倍。

Size 规格	W.L.L (t) 工作载荷(吨)	B.L (t) 破断载荷(吨)	Dimension (mm) 主要尺寸					N.W. (kg/pc) 净重(千克/件)
			Φ	E	H	K	L	
6-8	1.12	4.48	19	22	19	80	110	0.28
7/8-8	2	8	28	25	25	103	140.5	0.65
10-8	3.15	12.6	31	27.5	28	118	162	0.94
13-8	5.3	21.2	39	33	35	145	201	1.95
16-8	8	32	51	40	45	180	256	3.77
20-8	12.5	50	62	51	57	230	317	6.8
22-8	15	60	73	57	70	260	360	9.8
26-8	21.2	84.8	89	75	76	318	434	16.25
32-8	31.5	126	90	98	91	360	495.5	27.5

G80 Swivel Hook with Latch (TH-40)

G80旋转钩

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.

表面喷塑，颜色可选。
体上显示工作载荷。
最大保证载荷为工作载荷的2.5倍。
最小破断强度为工作载荷的4倍。

Size 规格	W.L.L (t) 工作载荷(吨)	B.L (t) 破断载荷(吨)	Dimension (mm) 主要尺寸							N.W. (kg/pc) 净重(千克/件)
			A	E	B	H	K	L	M	
6-8	1.12	5	32	22	17	9	109	137	16	0.34
7/8-8	2	8	42	21.5	35	15.8	150	192	21	1.02
10-8	3.15	12.8	42.5	26	35	15.8	162.5	208.5	23	1.24
13-8	5.3	21.6	48	32.5	39	18	191	246	31	3.60
16-8	8.0	32.8	62	43	53	25	243.5	313	34	4.66
20-8	12.5	50	68	49.5	51	28.5	276.5	363.5	41.5	7.40
22-8	15	60	79	54.5	65	32	332	431	55.7	10.6
26-8	21.2	84.8	105	81	114	40	429.5	545.5	70	21.4
32-8	31.5	126	105	100	96	40	465.3	596	76.2	32